



FORWARD MOTION THROUGH FORWARD THINKING®



HYDRO-GEAR°
COMMERCIAL



Hydro-Gear® Commercial engineered drive system

Robust powertrain designed for higher horsepower vehicles

Designed for up to 26" tires

Smooth drive performance

Unique design provides lower control forces

Longer life 16cc pump

Robust planetary gear reduction

Exclusive transport speed option for maximum efficiency


Innovative design reduces leak points



Designed for maintenance with an easily accessible internal oil filter

Maintenance free internal wet disc brake

Industry leading warranty and service support



SPECIFICATIONS		ZT-5400	
Low Speed Overall Reduction		18.6:1	23.1:1
High Speed Overall Reduction		12.9:1	16.0:1
Pump Displacement	in³/rev [cc/rev]	0.97 [16]	
Motor Displacement	in³/rev [cc/rev]	1.33 [21.8]	
Input Speeds Maximum Hi-Idle [No Load] Minimum [Loaded]	rpm rpm	3600 1800	
Output Torque Continuous Intermittent	lb-ft [N-m] lb-ft [N-m]	260 [352] 525 [711]	325 [440] 650 [880]
Weight on Tires (per unit) Maximum with 23" tires Maximum with 24" tires Maximum with 26" tires	lb [kg] lb [kg] lb [kg]	800 [363] 800 [363] 700 [317]	800 [363] 800 [363] 700 [317]
Axle Shaft Diameter	in [mm]	1.375 [34.925]	
Axle Shaft Options	Туре:	Tapered 4-Bolt Flange 5-Bolt Flange	
Parking Brake Type		Internal Wet Disc Brake	
Weight of Unit	lb [kg]	57 [25.85]	

Specifications subject to change without notice.

